


P-TYPE® Secondary Belt Cleaner

Reliable Secondary Belt Cleaner

The Flexco P-Type® Secondary Belt Cleaner is compact and designed to be positioned just off the head pulley to remove carryback from the belt. Stand alone, or when used in conjunction with a precleaner, the P-Type cleaner is a reliable choice for maintaining a highly efficient cleaning system.



Features and Benefits

- **Cleaning efficiency of metal blades.** The thin, hard edges of the metal blades deliver high cleaning efficiency and long wear life.
- **Works with Flexco mechanical splices.** The C-Tip tungsten carbide blades are impact-resistant, and the spring cushion allows them to move away from a passing splice without damage and with minimal cleaning disruption. V-Tip can be used only on vulcanized belts.
- **A complete cleaning system.** When the P-Type is teamed with a primary cleaner the system provides maximum cleaning power for tough applications.
- **Fits most conveyor structures.** Available for belt widths from 18" to 72" (450 mm to 1800 mm).

P-TYPE® Secondary Belt Cleaner

Specifications and Guidelines

Maximum Belt Speed

1000 FPM (5 M/sec)

Temperature Rating

-30° F to 180° F (-35° C to 82° C)

Usable Blade Wear Length

3/8" (9 mm)

Blade Material


Impact resistant, long-lasting tungsten carbide (C-Tip for mechanical fasteners, V-Tips for vulcanized belts)

Available for Belt Widths

18" to 72" (450 to 1800mm)

CEMA Cleaner Rating

Class 4




Pole Length

Cleaner size up to 48" (1200mm) + 30" (750mm) / Cleaner size 54" and up (1350mm) + 34" (850mm)

Maximum Conveyor Span

Cleaner size up to 48" (1200mm) + 25" (625mm) / Cleaner size 54" and up (1350mm) + 29" (725mm)



Horizontal Clearance Required

4" (100mm)

Vertical Clearance Required

8" (200mm)

Ordering Information

P-Type® Secondary with C-Tips*

Belt Width		Ordering Number	Item Code
in.	mm		
18	450	PC18	74566
24	600	PC24	74567
30	750	PC30	74568
36	900	PC36	74569
42	1050	PC42	74570
48	1200	PC48	74571
54	1350	PC54	74572
60	1500	PC60	74573
72	1800	PC72	74574

*NOTE: C-Tips can be used on mechanically spliced and vulcanized belts. P-Type cleaners come standard with Select Set™ Tensioners.

P-Type® Secondary with V-Tips*

Belt Width		Ordering Number	Item Code
in.	mm		
18	450	PV-18	78453
24	600	PV-24	78415
30	750	PV-30	78417
36	900	PV-36	78419
42	1050	PV-42	78421
48	1200	PV-48	78423
54	1350	PV-54	78454
60	1500	PV-60	78455
72	1800	PV72	73438

*NOTE: V-Tips can be used ONLY on vulcanized belts. P-Type cleaners come standard with Select Set™ Tensioners.

Replacement Tips

Ordering Number	Item Code
ICT6	74535
PSA150	73156

Lead time: 1 working day

Tips Required per Cleaner Size

in.	18	24	30	36	42	48	54	60	72
mm	450	600	750	900	1050	1200	1350	1500	1800
C-Tips or V-Tips Required	3	4	5	6	7	8	9	10	12

Additional Information

For size restricted applications, see the P-Type LS (Limited Space) Sell Sheet X2479.



Authorized Distributor:



2525 Wisconsin Avenue • Downers Grove, IL 60515-4200 • USA
Tel: (630) 971-0150 • Fax: (630) 971-1180 • E-mail: info@flexco.com

Visit www.flexco.com for other Flexco locations and products.

©2015 Flexible Steel Lacing Company. 11/15. For Reorder: X2397

